FOR INSURANCE COMPANY USE

ZIP CODE

BASE FLOOD ELEVATION (In AO Zones, Use Depth)

91387

POLICY NUMBER

STATE

CA

feet NGVD. (Elevation datum used must be the same as that on the FIRM.)

FIRM ZONE

40

*7*5.0

COMPANY NAIC NUMBER

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

FLOODPROOFING CERTIFICATE

FOR NON-RESIDENTIAL STRUCTURES

The floodproofing of non-residential buildings may be permitted as an alternative to elevating to or above the Base Flood Elevation; however, a floodproofing design certification is required. This form is to be used for that certification. Floodproofing of a residential building does not alter a community's floodplain management elevation requirements or affect the insurance rating unless the community has been issued an exception by FEMA to allow floodproofed residential basements. The permitting of a floodproofed residential basement requires a separate certification specifying that the design complies with the local floodplain management ordinance.

SECTION I FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

SECTION II FLOODPROOFING INFORMATION (By a Registered Professional Engineer or Architect)

DATE OF FIRM INDEX

9-29-89

(NOTE: for insurance rating purposes, the building's floodproofed design elevation must be at least one foot above the Base Flood Elevation to receive rating credit. If the building is floodproofed only to the Base Flood Elevation, then the building's insurance rating will result in a higher

and/or Bidg. Number) OR P.O. ROUTE AND BOX NUMBER

AMCH

SUFFIX

BUILDING OWNER'S NAME

Provide the following from the proper FIRM:

Floodproofing Design Elevation Information:

Building is floodproofed to an elevation of .

PANEL NUMBER

Height of floodproofing on the building above the lowest adjacent grade is

0480

COMMUNITY NUMBER

060729

premium.)

SECTION III CERTIFICATION (By Registered Professional Engineer or Architect)
Ion-Residential Floodproofed Construction Certification:
I certify that, based upon development and/or review of structural design, specifications, and plans for construction, the design and methods of construction are in accordance with accepted standards of practice for meeting the following provisions:
The structure, together with attendant utilities and sanitary facilities, is watertight to the floodproofed design elevation indicated above, with walls that are substantially impermeable to the passage of water.
All structural components are capable of resisting hydrostatic and hydrodynamic flood forces, including the effects of buoyancy, and anticipated debris impact forces.
I certify that the information on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.
ERTIFIER'S NAME WILLIAM J. RENO ZE197 PROFESSIO
CIVIL ENGR WRA ENGINGERING, INC.
DIRESS 24933 AVENUE STANFORO VALENCIA CA 91355 No. 28197 GNATURE DATE PHONE
Wike 3-26-08 661-295-3590 03-31-2010
Copies should be made of this Certificate for: 1) community official, 2) Insurance agent/company, and 3) building owner.
EMA Form 81-65, AUG 99 Replaces all previous editions F-056 TO SECALIFOR COM MENTS: 1, FLOOD VENTING 24 VENTS = 3072 SQ. INI. 2. 1' ADDITIONAL FROSEBOARD PROVIDED PER CRS REQUIREMENTS
2. I' ADDITIONAL FRUITBOARD PROVIDED PER CRS REGUIREMENTS